

ORDER FORM

ORDER e: roofsales@ultraframe.co.uk

QUOTE e: quotes@ultraframe.co.uk

New Build Replacement Project

PLAN VIEW

ACCOUNT No.

Company Name

Order Number

JOB REFERENCE

Company Contact

Telephone No.

Email

Delivery Address

.....

.....

POSTCODE

Delivery Date Req

Quotation Ref

FRONT ELEVATION

CRITICAL INFORMATION

***Required for structural snow / wind loading**

*Site Postcode

Roof Pitch (°)

Roof height restriction

Frame width

CUSTOMER NOTE: Please carefully read the Livingroof installation guide before filling in order details.

HOW TO PLACE AN ORDER FOR LIVINROOF:

LEFT ELEVATION

RIGHT ELEVATION

1. Sketch plan & elevations.
(If necessary, attach photos of existing property. Indicate on drawings if any part of project is existing).
2. Mark and caption the positions of all walls, brick piers, windows/doors, cut outs / intrusions.
3. Mark the preferred positions of any
 - a) roof windows
 - or b) rectangular glazed panels.
4. Upon placement of your Livingroof order, an order confirmation is generated which must be signed and emailed back.

Job No.:3598

Please sign and return to
roofsales@ultraframe.co.uk

SIGNED

DATE

ORDER FORM

JOB REFERENCE

ROOF INFORMATION

- On Fascia Below Fascia* Full Height Walls

If fitting to a bungalow please indicate Soffit Depth

*N.B. **Below fascia** is always on boxgutters, 30mm frame add on is needed but not supplied.

EAVES BEAM

- Standard (VAAAH)
 Structural (SEB)
 Gable beam
(MUST be used with Cornice)

If using SEB please indicate span and location of doors on drawing.

INTERNAL PELMET

- Specify with this order Upgrade with retro fit Standard Width (300-600mm) Other (600-1200mm)

Original roof job no. if applicable:

Please state (mm):

EXTERNAL PANEL

- U-Tec through colour composite (to match 7016) Aluminium powder coated sandwich (to match 7016)

CORNICE

- Style 1 Tier 2 Tier 3 Tier Curved

- Colour White Urban Grey Deeplas White Landmark Green Pure Cream RAL/BS Colour
- RAL 9003, RAL 7016, INTERPON SC050E, BS14C35, RAL 1015,
- GLOSS 80% GLOSS 30% GLOSS 80% GLOSS 80% GLOSS 30% Gloss %

CONSERVAGLASS OPTIONS - BLACK WARM EDGE SPACER

TIER 1 - CONSERVAGLASS

- C'Glass SMG Blue C'Glass SMG Neutral
 C'Glass SMG Bronze C'Glass SMG Aqua

TIER 2

- C'Glass 4S Blue C'Glass 4S Neutral
 C'Glass 4S Bronze C'Glass 4S Aqua

TIER 3

- C'Glass SMG
Ultimate Blue

TIER 4

- C'Glass SMG
Ultra83 Blue

ROTABOND SEALANT - MS POLYMER

- Black (NCGS001B) No. Tubes Req:.....
N.B. For use with Conservaglass

CONSERVAFLASH

- Soaker Only
 Yes

ROOF VENTS AND MECHANISM (mark plan)

- Brass Manual Spindle Manual Spindle and pole Manual Spindle and telescopic pole

- Chrome Manual Spindle Manual Spindle and pole

- Electric motor with digital thermostat and rain sensor Electric motor and rocker switch
 Electric motor with radio and remote control Electric motor with thermostat (AVTD002)
 Electric without switch/thermostat (Motor only)

ANCILLARY EXTRAS

IMPORTANT NOTE 1

The installer is responsible for ensuring that where Livinroof is supported by means such as timber frame walls, the structure provides enough lateral support and resistance to wind uplift. Further guidance can be obtained through our system overview. Ultraframe cannot be responsible for the structural adequacy of any existing building work used as part of an overall conversion. While assistance is provided, ultimate responsibility to secure Building Regulations / approvals lies with the retail installer.

IMPORTANT NOTE 2

U-Design is the final arbiter on price and specification decisions.

IMPORTANT NOTE 3

The Livinroof components have been designed and manufactured to meet the specification of each individual job. Any significant on site modifications particularly relating to the repositioning of any structural members will invalidate the product's warranty and compromise the structures integrity. If adjustments are required due to site conditions please consult Ultraframe. Tie Bars / Tie Beams will be specified by Ultraframe and will appear on your confirmation. Always check the confirmation carefully.

Job No.:3598

Please sign and return to

roofsales@ultraframe.co.uk

SIGNED

DATE