

ORDER FORM



ORDER e: roofsales@ultraframe.co.uk

QUOTE e: quotes@ultraframe.co.uk

New Build

Replacement Project

PLAN VIEW

ACCOUNT No.

Company Name

Order Number

JOB REFERENCE

Company Contact

Telephone No.

Email

Delivery Address

POSTCODE

Delivery Date Req

Quotation Ref

CRITICAL INFORMATION

***Required for structural snow / wind loading**

*Site Postcode

Roof pitch

Fixed at 25°

FRONT ELEVATION

CUSTOMER NOTE: Please carefully read the Ultrasky Roof installation guide before filling in order details.

HOW TO PLACE AN ORDER FOR ULTRASKY ROOF:

1. Sketch plan & elevations.
(If necessary, attach photos of existing property. Indicate on drawings if any part of project is existing).
2. Mark and caption the positions of all walls, brick piers, windows/doors, cut outs / intrusions.
3. Mark the preferred positions of any
 - a) roof windows
 - or b) rectangular glazed panels.
4. Upon placement of your Ultrasky Roof order, an order confirmation is generated which must be signed and emailed back.

LEFT ELEVATION

RIGHT ELEVATION

Job No.:3598

Please sign and return to
roofsales@ultraframe.co.uk

SIGNED

DATE

JOB REFERENCE

ROOF / SITE INFORMATION	ROOF COLOUR	White	Matt Grey	Bespoke RAL/BS Colour
Frame Width	External		
	Internal		

INTERNAL PELMET

Minimum Width (300mm)	Other (300-1200mm) Please state (mm):
-----------------------	---------------------------------------

ROOF / INFORMATION

On Fascia*	Below Fascia	If fitting to a bungalow please indicate Soffit Depth.....
Full Height Walls		

Please state on drawing / style and dimensions.

N.B. If order is retro fit then option of on fascia is the only option available.

TOP CAPPINGS	TIE BARS	CONSERVAFLASH	BAR UNDERCLADDINGS
Dome (PVCu)	White Tie Strut	Soaker Only	Standard (PVCu)
Aluminium		Yes	Aluminium

CORNICE					EAVES BEAM
Style	1 Tier	2 Tier	3 Tier	Curved	Standard (VAAAH)
Colour	White	Matt Grey	Deeplas	RAL/BS Colour	Structural (SEB)
					If using SEB please indicate span and location of doors on drawing.

ROTABOND SEALANT - MS POLYMER

White (NCGS001W)	Black (NCGS001B)	No. Tubes Req:	N.B. For use with Conservaglass
------------------	------------------	----------------------	---------------------------------

ROOF VENTS AND MECHANISM (mark plan)

PVCu Internal Cladding	Aluminium Internal Cladding		
Brass	Manual Spindle	Manual Spindle and pole	Manual Spindle and telescopic pole
Chrome	Manual Spindle	Manual Spindle and pole	
Electric motor with digital thermostat and rain sensor		Electric motor and rocker switch	
Electric motor with radio and remote control		Electric motor with thermostat (AVTD002)	
Electric without switch/thermostat (Motor only)			

GLASS OPTIONS - WARM EDGE SPACER

Tier 3		Tier 2		Tier 1	
Conservaglass	<input type="checkbox"/> Ultimate Blue	<input type="checkbox"/> Blue 4S	Bronze 4S	<input type="checkbox"/> Std Blue	Std Bronze
		Neutral 4S	Clear 4S	Std Neutral	Std Clear
Unglazed					

ANCILLARY EXTRAS

Job No.:3598