

Order / Quote Form

☐ **ORDER**

☐ **QUOTE**

ACCOUNT No.

Date:

Company Name:

Order Number:

JOB REFERENCE:

Installer Company Name

Company Contact:

Telephone No:

Email:

Delivery Address:

Postcode:

Delivery Date Req:

Quotation Ref:

CRITICAL INFORMATION

* **Site Postcode** (required for structural snow / wind loading)

Postcode:

How to place an order for Flat Roof:

STEP 1: DRAW YOUR ROOF

Draw a diagram of the roof with the external base size, internal apertures, mark off outlets and any soil pipes.

Please label each elevation as per your plan drawing (A, B, C, etc). For all elevations please include wall and frame thickness in mm (where applicable).

Please mark the apertures on the plan along with the dimensions for the aperture, internal size. Please use the key below to mark your apertures e.g. a lantern and/ or flat skylight.

Please mark any outlets and soil pipes, add on any dimensions.

If possible, please send any photo's or additional plans to your order.

KEY



Lantern



Outlets / Downpipes



Flat Skylight



Soil pipe

Draw Roof

External base size unlimited widths and projections of up to 5m. The Flat Roof is only available on square / rectangles sizes. Small intrusions like soil pipes are available but chimney breasts are not. Maximum soil pipe size is 266mm. You can specify 0, 1 or 2 apertures. Maximum: front opening up to 5670mm and side up to 3220mm.



Order / Quote Form

JOB REFERENCE:

STEP 2: MARK YOUR ELEVATIONS AND INDICATE THE FOLLOWING:

Please mark on the drawing plan below

- What the roof is sitting on e.g. frame or brick
- Thickness of frame or brick
- Height of wall - standard eaves height is 2400mm unless specified.
- Opening location and size

If you would like a visual representation of your design, please confirm the colours of your frames.

If structural posts are needed, would you like Ultraframe to supply yes no

Order / Quote Form

JOB REFERENCE:

STEP 3: SPECIFY YOUR LANTERN / FLAT SKYLIGHT

Lantern

ROOF MATERIALS

PVCu White	PVCu Painted Grey	PVCu Black	Aluminium 9003 White 80% gloss	Aluminium 7016 Grey 30% gloss	Aluminium 9005 Black 60% gloss
---------------	----------------------	---------------	-----------------------------------	----------------------------------	-----------------------------------

External

Internal

BESPOKE COLOUR

PVCu	Ali	
		RAL
		RAL

External

Internal

GLASS OPTIONS - WARM EDGE SPACER

Super Energy Saving Glass

Low Solar Gain ☐ Ultimate Blue Aqua 4S	Medium Solar Gain ☐ Bronze 4S Blue 4S Neutral 4S	High Solar Gain Clear 4S
--	---	------------------------------------

Good Thermal Efficiency

Low Solar Gain ☐ Std Aqua	Medium Solar Gain ☐ Std Bronze Std Blue Std Neutral	High Solar Gain Std Clear
--	--	-------------------------------------

ROTABOND SEALANT - MS POLYMER

Black (NCGS001B) No. Tubes Req: N.B. For use with glass

ROOF VENTS AND MECHANISM

Roof vent up to ridge

Roof vent with glass above

Manual with brass

Manual with chrome

Electric switch/mechanism

Electric with rain sensor / thermostat

Flat Skylight

COLOUR: RAL9005 - 60% Black RAL9003 - 80% White RAL7016 - 30% Grey Bespoke RAL: GLOSS %

GLASS OPTIONS: Standard, 26mm or 28mm (glass size dependent on skylight size)

Clear

Blue

STEP 4: CHOOSE YOUR SOFFIT

Please specify if you would like standard soffit or extended soffit.

Standard soffit

Extended soffit



Standard soffit



Extended soffit

STEP 5: FASCIA OPTION

Please specify what fascia option you would like.


Naked

Classic Fascia

Curved Cornice

Two Tier Flat Cornice

Four Tier Flat Cornice
(only available on standard soffit)



STEP 5A: PICK YOUR FASCIA COLOUR

Please specify your fascia, gutter and cornice colour.

Fascia and gutter colour White Other:

Cornice colour White Other:

Please note that roof membrane is not supplied and must be ordered separately. The Flat Roof System is compatible with most roof finishes such as GRP, EPDM or PVC membranes.

Please return to

flatroofsales@ultraframe.co.uk

Job No.:3598, Page 3 of 6

hup!
The better way to build

Base DPC is usually 22mm below the back door sill if aligning foot levels with the house.

This image shows a full page of blank graph paper. The grid consists of small, equal-sized squares formed by thin, light gray lines. There are 20 columns and 20 rows of these squares, creating a total of 400 square units. The lines are evenly spaced both horizontally and vertically, providing a standard template for technical drawing or mathematics.

Job No. 3598 / Page 4 of 6

Order Form



2. Elevations

Please draw each elevation of your hup! walls marking the elevations clearly with A, B, C, D etc. Include window and doors sizes and distance from the eaves as well as the floor clearly.

Tick this box if you require the cable management panel which is supplied on all panels above 560mm.

Order Form

3. Wall Finishes

The type of wall finish can change the sequence of the battens and calcium silicate board, please tick the wall finish for this project?

Brick Slips Steel façade (Boundary only) Render External Cladding - Type

4. Walling kit

Please tick the box to confirm which elements of the walling kit you will require to be supplied by Ultraframe.

None - I am supplying my own	Ventilation trim only
Aperture trim only	Batten kit (includes battens and fixings)
Render Board kit (includes ventilation trim, aperture trims and battens)	
Brick Slip Rails (includes trims, battens and render Board. Brick slips not supplied)	

5. Aperture Trim Colour

White Smooth Grey Light Oak Rosewood

Surveyor's Details

If you would like us to liaise with your surveyor on this hup! order, please put contact details below.

NAME:

CONTACT NO:

EMAIL ADDRESS: