

# Order / Quote Form

☐

ORDER

☐

QUOTE

ACCOUNT No.

Date:

Company Name:

Order Number:

JOB REFERENCE:

Installer Company Name

Company Contact:

Telephone No:

Email:

Delivery Address:

Postcode:

Delivery Date Req:

Quotation Ref:

CRITICAL INFORMATION

\* Site Postcode (required for structural snow / wind loading)

Postcode:

## Draw Roof

External base size unlimited widths and projections of up to 5m. The Flat Roof is only available on square / rectangles sizes. Small intrusions like soil pipes are available but chimney breasts are not. Maximum soil pipe size is 266mm. You can specify 0, 1 or 2 apertures. Maximum: front opening up to 5670mm and side up to 3220mm.

## How to place an order for Flat Roof:

STEP 1: DRAW YOUR ROOF

Draw a diagram of the roof with the external base size, internal apertures, mark off outlets and any soil pipes.


Please label each elevation as per your plan drawing (A, B, C, etc). For all elevations please include wall and frame thickness in mm (where applicable).


Please mark the apertures on the plan along with the dimensions for the aperture, internal size. Please use the key below to mark your apertures e.g. a lantern and/ or flat skylight.


Please mark any outlets and soil pipes, add on any dimensions.


If possible, please send any photo's or additional plans to your order.

KEY

Lantern

Flat Skylight

Outlets / Downpipes

Soil pipe

# Order / Quote Form

JOB REFERENCE:

STEP 2: MARK YOUR ELEVATIONS AND INDICATE THE FOLLOWING:

Please mark on the drawing plan below

- What the roof is sitting on e.g. frame or brick
- Thickness of frame or brick
- Height of wall - standard eaves height is 2400mm unless specified.
- Opening location and size

If you would like a visual representation of your design, please confirm the colours of your frames.

If structural posts are needed, would you like Ultraframe to supply      yes      no

# Order / Quote Form

## JOB REFERENCE:

### STEP 3: SPECIFY YOUR LANTERN / FLAT SKYLIGHT

#### Lantern

##### ROOF MATERIALS

PVCu  
White

PVCu  
Painted Grey

PVCu  
Black

Aluminium 9003  
White 80% gloss

Aluminium 7016  
Grey 30% gloss

Aluminium 9005  
Black 60% gloss

External

Internal

##### BESPOKE COLOUR

PVCu

Ali

External

RAL

Internal

RAL

##### GLASS OPTIONS - WARM EDGE SPACER

###### Super Energy Saving Glass

###### Low Solar Gain

☐ Ultimate Blue

Aqua 4S

###### Medium Solar Gain

☐ Bronze 4S

Blue 4S

Neutral 4S

###### High Solar Gain

Clear 4S

###### Good Thermal Efficiency

###### Low Solar Gain

☐ Std Aqua

###### Medium Solar Gain

☐ Std Bronze

Std Blue

Std Neutral

###### High Solar Gain

Std Clear

##### ROTABOND SEALANT - MS POLYMER

Black (NCGS001B)

No. Tubes Req:

N.B. For use with glass

##### ROOF VENTS AND MECHANISM

Roof vent up to ridge

Roof vent with glass above

Manual with brass

Manual with chrome

Electric switch/mechanism

Electric with rain sensor / thermostat

#### Flat Skylight

COLOUR: RAL9005 - 60% Black

RAL9003 - 80% White

RAL7016 - 30% Grey

Bespoke RAL:

GLOSS %

GLASS OPTIONS: Standard, 26mm or 28mm (glass size dependent on skylight size)

Clear

Blue

### STEP 4: CHOOSE YOUR SOFFIT


Please specify if you would like standard soffit or extended soffit.

Standard soffit

Extended soffit



Standard soffit



Extended soffit

### STEP 5: FASCIA OPTION

Please specify what fascia option you would like.


Naked

Classic Fascia

Curved Cornice

Two Tier Flat Cornice

Four Tier Flat Cornice  
(only available on standard soffit)



### STEP 5A: PICK YOUR FASCIA COLOUR

Please specify your fascia, gutter and cornice colour.

Fascia and gutter colour

White

Other:

Cornice colour

White

Other:

**Please note that roof membrane is not supplied and must be ordered separately. The Flat Roof System is compatible with most roof finishes such as GRP, EPDM or PVC membranes.**

Please return to

[flatroofsales@ultraframe.co.uk](mailto:flatroofsales@ultraframe.co.uk)

Job No.:3598, Page 3 of 6

hup!<sup>®</sup>  
The better way to build

Base DPC is usually 22mm below the back door sill if aligning floor levels with the house.

A full-page sheet of white graph paper featuring a uniform grid of thin, light gray horizontal and vertical lines. The grid consists of small squares covering the entire area of the page.

## Job No. 3598 / Page 4 of 6

# Order Form



## 2. Elevations

Please draw each elevation of your hup! walls marking the elevations clearly with A, B, C, D etc. Include window and doors sizes and distance from the eaves as well as the floor clearly.

Tick this box if you require the cable management panel which is supplied on all panels above 560mm.

# Order Form

### 3. Wall Finishes

The type of wall finish can change the sequence of the battens and calcium silicate board, please tick the wall finish for this project?

## Brick Slips

Render

External Cladding - Type .....

#### 4. Walling kit

Please tick the box to confirm which elements of the walling kit you will require to be supplied by Ultraframe.

None - I am supplying my own

Ventilation trim only

Aperture trim only

Batten kit (includes battens and fixings)

Render Board kit (includes ventilation trim, aperture trims and battens)

Brick Slip Rails (includes trims, battens and render Board. Brick slips not supplied)

## 5. Aperture Trim Colour

White

Smooth Grey

Light Oak

Rosewood

### Surveyor's Details

If you would like us to liaise with your surveyor on this hup! order, please put contact details below.

NAME:

**CONTACT NO:**

EMAIL ADDRESS: