

ORDER FORM

ORDER e: partsales@ultraframe.co.uk

QUOTE e: quotes@ultraframe.co.uk

New Build

Existing flat roof

Fill in the dimensions in the boxes below.

- Please note all dimensions are to the internal face of the kerb (excluding plasterboard).
- Measurement size of kerb height needs to be minimal 150mm (internal aperture).
- Slope / width is always the smallest size.

ACCOUNT No.

Company Name

Order Number

JOB REFERENCE

Company Contact

Telephone No.

Email

Delivery Address

POSTCODE

Delivery Date Req

Quotation Ref

ROOF SPECIFICATION

COLOUR: RAL9005 - 60% Black

RAL9003 - 80% White

RAL7016 - 30% Grey

Bespoke RAL:

GLOSS %:

PITCH: 4°

CONSERVAGLASS OPTIONS: Standard, 26mm or 28mm (glass size dependent of skylight size)

Clear

Blue

CUSTOMER NOTE: Please carefully read the Ultrasky Flat Skylight installation guide before filling in order details.

The minimum distance between flat skylights is 400mm

Glass Specification: The glass is either 26mm or 28mm depending on the size of the flat skylight. See price list for details. Available in Clear and Blue glass options.

Outer Layer - 6mm Clear/Blue Toughened / 16mm Argon filled cavity with warm edge spacer.

Inner Layer - 4mm or 6mm (size dependent) high performance, Low E, toughened.

Glass U-value: 1.0

Inner panes on glass units must be laminated in applications more than 5 metres above floor level or are located over a body of water

DISCLAIMER

The builder/installer is responsible for providing / checking structural deck. Building Regulation applications MAY be needed depending upon application.

In certain commercial applications, restrictions in the use of the product may apply. **Not suitable to walk on the glass.**

Contact 01200 452918 for guidance.

Job No.:3598

Please sign and return to

partsales@ultraframe.co.uk

SIGNED

DATE

Note: Upon placement of your Ultrasky Flat Skylight order, no drawing confirmation will be sent so please ensure information provided is accurate.

